Exhibit 3.7

Information Request No. 39

CONFIDENTIAL BUSINESS INFORMATION

Pursuant to 40 CFR Part 2, Subpart B, Monsanto Company hereby asserts a business confidentiality claim covering this Exhibit and all documents attached thereto.

AMERICAN BOTTOMS REGIONAL WASTEWATER TREATMENT FACILITY

1 AMERICAN BOTTOMS ROAD SAUGET, ILLINOIS 62201 (618) 337-1710

FAX (618) 337-8919

VILLAGE OF SAUGET

AMERICAN BOTTOMS REGIONAL
WASTEWATER TREATMENT FACILITY

WASTEWATER DISCHARGE PERMIT

for

MONSANTO COMPANY

PERMIT NO. 92-105

VILLAGE OF SAUGET AMERICAN BOTTOMS REGIONAL WASTEWATER TREATMENT FACILITY WASTERWATER DISCHARGE PERMIT NO. 92-105

TABLE OF CONTENTS

Wastewater Dis	scharge Permit No. 92-105	1
PART 1 - GENER	RAL CONDITIONS OF PERMIT	2
Α.	General	2
В.	Prohibitive Standards	2
С.	Prohibition of Improper Dilution	2
D.	Duration	2
Ε.	Transfer	2
F.	Change in Conditions	2
G.	Access	2 2 2 2 2 2 2 2 3 4 4
н.	Retention of Records	3
I.	Analytical Methods	4
J.	Pretreatment Facilities	4
к.	Spill Containment	4
L.	Permit Modifications	4
М.	Civil and Criminal Penalties	5
N.	Additional Information	4 5 5 6
0.	Upset	5
Ρ.	Bypass	6
Q.	Resampling	6
Ř.	Notifications	6
S.	Report Submittal	7
-		
PART 2 - GENER	RAL AND SPECIFIC REPORTING REQUIREMENTS	8
Α.	General	
В.	Specific	8
	1. Monitoring Reports	8
	2. Compliance Deadline Report	8 8
	3. Quarterly Supplemental Progress Report	8
	3. 2413311, 319313111111111111111111111111111	
PART 3 - GENER	RAL SAMPLING AND TESTING REQUIREMENTS	9
האחת א הייידיני	IPME CINTENDIONE CANDIINO AND MECHINO DEGILDEMENTO	1 7
	JENT LIMITATIONS, SAMPLING AND TESTING REQUIREMENTS .	11
Α.	Local Limits	11
В.		11
<u>C</u> .	National Categorical Pretreatment Standards	1.
D.	Monitoring Schedule	14
DADE COMP	TANGE COMPANIE	1 4
	LIANCE SCHEDULE	16
Α.	General	16
В.	Final Compliance Date	
С.	Compliance Schedule for Ammonia-Nitrogen	16
FIGURE 1 - MON	NITORING LOCATION	1 -

AMERICAN BOTTOMS REGIONAL WASTEWATER TREATMENT FACILITY

1 AMERICAN BOTTOMS ROAD SAUGET, ILLINOIS 62201 (618) 337-1710 FAX (618) 337-8919

September 1, 1992

Monsanto Company - W.G. Krummrich Plant 500 Monsanto Avenue Sauget, Illinois 62206-1198

Wastewater Discharge Permit No. 92-105

Dear Sirs:

In accordance with all the terms and conditions of Ordinance 632 of the Village of Sauget; the 1977 Regional Agreement as amended; Section 46 of the Illinois Environmental Protection Act of 1970 (Ill. Rev. Stat. 1987. Ch. 1111/2, Sec. 1046) as amended; and Ill. Rev. Stat. 1987, Ch 24, Sec. 11-141-7; permission is hereby granted to Monsanto Company, operating under the Standard Industrial Classification (SIC) Code Nos. 2819, 2842, 2865, and 2869, and subject to the National Categorical Pretreatment Standard (NCPS) No. 40 CFR 414, Subparts G and H, to discharge industrial wastewater into sewer lines tributary to the American Bottoms Regional Wastewater Treatment Plant in accordance with and subject to the provisions of attached American Bottoms Regional Wastewater Discharge Permit No. 92-105 ("Permit").

This Permit is granted in response to the application filed on the 7th day of February, in the year 1992 in the office of the General Manager, #1 American Bottoms Road, Sauget, Illinois 62201, and in conformity with plans, specifications and other data submitted in support of the above application, all of which are filed with and considered as a part of this Permit, together with the attached conditions and requirements.

Nothing herein shall be construed as a permit or as permission for the permittee to violate the provisions of any sewer use ordinance in effect within the jurisdiction of any unit of local government in which the permittee's facility is located.

This Permit will take effect on the 1st day of September in the year 1992, and will expire on the 1st day of September in the year 1994.

By: Styll Scheller

1

PART 1 - GENERAL CONDITIONS OF PERMIT

- A. General This Wastewater Discharge Permit shall be express-ly subject to all provisions of Ordinance 632 of the Village of Sauget (hereinafter "the Ordinance") and all other applicable regulations, user charges, and fees established by the Village of Sauget. In consideration of the granting of this Permit, the permittee shall comply with all provisions of the Ordinance, Permit conditions, and the Implementation procedures including, but not limited to the specific requirements of these General Condition Articles. Any Permit noncompliance constitutes a violation of the Ordinance, and is grounds for enforcement action.
- B. Prohibitive Standards The permittee shall comply with all prohibitive discharge standards pursuant to Section 3.2 of the Ordinance and all Local, State, and Federal discharge limits set forth in the Permit.
- C. <u>Prohibition of Improper Dilution</u> Improper dilution shall be prohibited pursuant to Section 3.6 of the Ordinance.
- D. <u>Duration</u> This Permit is issued effective September 1, 1992, and shall expire on September 1, 1994.
- E. Transfer Pursuant to Section 4.11 of the Ordinance, this Wastewater Discharge Permit may be reassigned or transferred, in whole or in part, to a new owner and/or operator only if the permittee gives at least thirty (30) days advance notice to the POTW and the POTW approves the Wastewater Discharge Permit transfer. The notice to the POTW must include a written certification by the new owner and/or operator which:
 - 1. States that the new owner and/or operator has no immediate intent to change the facility's operations and processes;
 - 2. Identifies the specific date on which the transfer is to occur; and
 - 3. Acknowledges full responsibility for complying with the Wastewater Discharge Permit.
- F. Change in Conditions Pursuant to Section 4.7 of the Ordinance, in the event the type, quality, character or volume of Pollutants in a Discharge, including the listed or characteristic hazardous wastes for which the permittee has

submitted initial notification under Section 4.13.5 of the Ordinance, is expected to substantially change as reasonably determined by the permittee or POTW, the permittee or his assignee (see paragraph E. above) shall give sixty (60) days advance notice in writing to the POTW and shall make a new application to the POTW and the Sewer System Owner prior to said change. No permittee shall substantially change the type, quality, character or volume of its Wastewater beyond that allowed by this Permit without prior approval of the Sewer System Owner and the POTW.

- G. Access Pursuant to Section 4.15 of the Ordinance, persons or occupants of premises in which a Discharge source or treatment system is located or in which records are kept shall allow the POTW or its representative ready access upon presentation of credentials at reasonable times to all parts of said premises for the purposes of inspection, sampling, examination and photocopying of records required to be kept by the Ordinance and this Permit, and in the performance of any of their duties. The POTW shall have the right to set up on the permittee's property such devices as are necessary to conduct sampling, monitoring and metering operations.
- H. Retention of Records Pursuant to Section 4.15 of the Ordinance, the permittee shall maintain records of all information resulting from any monitoring activities required by this Ordinance and shall include:
 - 1. The date, exact place, method and time of sampling and the names of the Person or Persons taking the samples;
 - 2. The dates analyses were performed;
 - 3. Who performed the analyses;
 - 4. The analytical techniques/methods used; and
 - 5. The results of such analyses.

The permittee shall maintain for inspection by the POTW, IEPA or USEPA such records for a minimum of three (3) years. This period of retention shall be extended during the course of any unresolved litigation regarding the Discharge of Pollutants by the permittee or operation of the POTW Pretreatment program or when requested by the Regional Administrator of USEPA or the Director of IEPA.

- I. Analytical Methods - All measurements, sampling, tests, and analyses to which reference is made in this Permit shall be determined and performed in accordance with the procedures established by the Administrator of the United States Environmental Protection Agency (hereafter "Administrator") pursuant to Section 304(q) of the Act and contained in 40 CFR Part 136 and amendments thereto or with any other test procedures approved by the Administrator. Sampling shall be performed in accordance with the techniques approved by the Administrator. Where 40 CFR Part 136 does not include sampling or analytical techniques for the Pollutants in question, or where the Administrator determines that the Part 136 sampling and analytical techniques are inappropriate for the Pollutant in question, sampling and analyses shall be performed using validated analytical methods or any other sampling and analytical procedures, including procedures suggested by the POTW or other parties, approved by the Administrator.
- J. Pretreatment Facilities The permittee shall provide necessary Wastewater Pretreatment as required to comply with the Ordinance and shall achieve compliance with all applicable Pretreatment Requirements and Standards within the time limitations as specified by appropriate statutes, regulations, and the Ordinance. Any facilities required to pretreat Wastewater to a level acceptable to the POTW shall be provided, properly operated and maintained at the permittee's expense. Such Pretreatment facilities shall be under the control and direction of an IEPA certified Wastewater Treatment Operator.
- K. Spill Containment Pursuant to Section 3.7 of the Ordinance, any permittee having the ability to cause Interference or Pass-Through of the POTW or to violate the regulatory provisions of the Ordinance shall provide protection from Accidental or Slug Discharges to the POTW of prohibited materials or other substances regulated by the Ordinance. Any facilities required to prevent Accidental or Slug Discharge of prohibited materials shall be provided and maintained at the permittee's own cost and expense.
- Permit Modifications The terms and conditions of this Permit may be modified by the POTW during the term of the Permit for good cause including, but not limited to, the following: to incorporate any new or revised Federal, State, or local Pretreatment Standards or Requirements; to address significant alterations or additions to the permittee's operation, processes, or Wastewater volume or charac-

ter since the time of Wastewater Discharge Permit issuance; a change in the POTW that requires either a temporary or permanent reduction or elimination of the authorized Discharge; misrepresentation or failure to fully disclose all relevant facts in the Wastewater Discharge Permit application or in any required reporting; revision of or a grant of variance from Categorical Pretreatment Standards pursuant to 40 CFR 403.13; to correct typographical errors in the Wastewater Discharge Permit; or to reflect a transfer of the facility ownership and/or operation to a new owner/operator (as provided in paragraph E. above). The permittee shall be informed of any proposed changes in its Permit at least 30 days prior to the effective date of any modification, and shall have all rights of appeal as provided in Section 4.12 of the Ordinance.

M. Civil and Criminal Penalties - Pursuant to Part 6 of the Ordinance, any permittee who is found to have violated an Order of the POTW or who has failed to comply with any provision of the Ordinance, and the orders, rules, and regulations and Wastewater Discharge Permits issued thereunder, may be fined by appropriate suit at law in an amount not less than one hundred dollars (\$100) nor more than one thousand dollars (\$1000) per day for each violation. In addition to the penalties provided herein, the POTW may recover reasonable attorney's fees, court costs, court reporter fees and other expenses of litigation by appropriate suit at law against the Person found to have violated this Ordinance or the orders, rules, regulations and Permits issued thereunder.

Any Person who knowingly makes any false statements, representation or certification in any application, record, report, plan or other document filed or required to be maintained pursuant to the Ordinance or Wastewater Discharge Permit, or who falsifies, tampers with, or knowingly renders inaccurate any monitoring device or method required under the Ordinance, shall in addition be guilty of a misdemeanor and upon conviction, be punished by a fine of \$500 to \$1,000, for each offense.

- N. Additional Information The permittee shall furnish any additional information as may be reasonably requested by the Village of Sauget from time to time.
- O. <u>Upset</u> Pursuant to Section 3.8 of the Ordinance, the permittee shall have an affirmative defense to an action brought for noncompliance with National Categorical Pre-

treatment Standards provided that the conditions of Section 3.8.3 of the Ordinance are met. In any enforcement proceeding, the permittee seeking to establish the occurrence of an Upset shall have the burden of proof.

- P. <u>Bypass</u> Bypass provisions pursuant to Section 3.9 of the Ordinance are applicable to this Permit and are hereby incorporated by reference.
- Q. Resampling Pursuant to Section 4.13.3.7 of the Ordinance, if sampling performed by the permittee indicates a violation, the permittee shall notify the POTW within 24 hours of becoming aware of the violation. The permittee shall also repeat the sampling and analysis and submit the results of the repeat analysis to the POTW within 30 days after becoming aware of the violation, except the permittee is not required to resample if:
 - 1. The POTW performs sampling at the permittee at a frequency of at least once per month, or
 - 2. The POTW performs sampling at the permittee between the time when the permittee performs its initial sampling and the time when the permittee receives the results of this sampling.

Resampling is only required for those parameters for which the violation has been identified.

- R. <u>Notifications</u> The following verbal and written notifications are required:
 - 1. Pursuant to Section 4.13.3.7 of the Ordinance, if sampling performed by the permittee indicates a violation of any requirements of the Ordinance or this Permit, the permittee shall notify the POTW within 24 hours of becoming aware of the violation. Such notification may be made orally by telephone.
 - 2. Pursuant to Section 3.7.4 of the Ordinance, in the case of an Accidental or Slug Discharge of Pollutants which may cause Interference at the POTW or may Pass Through the POTW or violate any other requirements of the Ordinance or this Permit, it shall be the responsibility of the permittee to immediately telephone and notify the POTW and the Sewer System Owner of the incident. The notification shall include name of caller, location and time of Discharge, type of Wastewater, estimated concentration and volume. For

permittees discharging to the P-Chem Plant, notice to the POTW only is required.

- 3. Within five days following an Accidental Discharge, the permittee shall submit to the POTW and the Sewer System Owner a detailed written report describing the cause of the Accidental Discharge and the measures to be taken by the permittee to prevent similar future occurrences.
- 4. A permittee wishing to establish the affirmative defense of Upset for noncompliance with National Categorical Pretreatment Standards shall, in addition to the 24-hour verbal notification required in 1. above, and under Section 3.8.3.3 of the Ordinance, provide a written submission containing the information required by Section 3.8.3.3 of the Ordinance within five days of becoming aware of the Upset.
- 5. Pursuant to Section 3.9.2.1 of the Ordinance, if the permittee knows in advance of the need for a Bypass, it shall submit prior written notice to the POTW, if possible at least ten days before the date of the Bypass.
- 6. Pursuant to Section 3.9.2.2 of the Ordinance, the permittee shall submit oral notice of an unanticipated Bypass that exceeds applicable Pretreatment Standards or Requirements to the POTW within 24 hours from the time the permittee becomes aware of the Bypass. A written submission meeting the requirements of Section 3.9.2.2 of the Ordinance shall also be provided to the POTW within 5 days of the time the permittee becomes aware of the Bypass.
- 7. Pursuant to Section 4.13.5.3 of the Ordinance, in the case of any new regulations under Section 3001 of RCRA identifying additional characteristics of hazardous waste or listing any additional substance as a hazardous waste, the permittee must notify the POTW, the EPA Regional Waste Management Division Director, and the State hazardous waste authorities of the Discharge of such substance within 90 days of the effective date of such regulations.
- S. Report Submittal All reports and/or notifications required by this Permit shall be submitted to:

Pretreatment Coordinator

American Bottoms Regional Telephone: (618) 337-1710

Wastewater Treatment Facility Facsimile: (618) 337-8919

#1 American Bottoms Road

Sauget, Illinois 62201

PART 2 - GENERAL AND SPECIFIC REPORTING REQUIREMENTS

- A. $\frac{\text{General}}{403.12}$ The General Pretreatment Regulations of 40 CFR $\frac{1}{403.12}$ and Ordinance 632 have set forth basic reporting requirements that apply to the permittee.
- B. <u>Specific</u> The specific reporting requirements of this Permit include the following reporting requirements:
 - 1. Monitoring Reports Monitoring results obtained shall be summarized and reported on a monthly basis. The report is due on or before 45 days after the end of the month in which the sampling was performed. The report shall indicate the nature and concentration of all pollutants in the wastewater discharges which are regulated by the standards set forth in this Permit and include measured maximum and average daily flows. These reports will satisfy the requirement for the Periodic Compliance Report, provided they contain all the information and certifications required pursuant to Section 4.13.3 of the Ordinance.
 - 2. Compliance Deadline Report Pursuant to Section 4.13.2 of the Ordinance, within ninety (90) days following the date for final compliance with any applicable Pretreatment Standards, or in the case of a New Source, within ninety (90) days following commencement of the Discharge of Wastewater into the POTW, any permittee subject to any Pretreatment Standards shall submit a report on compliance with any applicable Pretreatment Standards in a form prescribed and furnished by the POTW. This report shall contain information as described in Section 4.13.2.2 of the Ordinance.
 - 3. Quarterly Supplemental Progress Report Monsanto shall continue to administer their existing program for identifying the principal causes of remaining color in the American Bottoms Regional Wastewater Treatment Facility effluent, and for assessing possible color controls.

Documentation of the continued administration of this program shall be submitted in the form of a "Quarterly Supplemental Progress Report" (QSPR) which shall contain, as a minimum, available sampling results which have been received since the preparation of the previous quarterly submittal and to the extent reasonably feasible at the time of reporting, an assessment of the

effectiveness and implementability of any further color controls identified as a result of this program.

Submittal of the QSPR identified above for quarterly periods ending the last day of February, May, August, and November shall be required on the last business day during the month immediately following the end of the reporting period (i.e. March, June, September, and December).

PART 3 - GENERAL SAMPLING AND TESTING REQUIREMENTS

- A. The permittee is responsible for compliance sampling. The monitoring facilities designated by this Permit are shown on Figure 1.
- B. Compliance monitoring results and frequencies may be reviewed annually by the Village of Sauget and appropriate adjustments made to frequencies and parameters in a modified or revised Wastewater Discharge Permit.
- C. All handling and preservation of collected samples and laboratory analyses shall be performed in accordance with procedures contained in 40 CFR Part 136 and amendments thereto unless specified otherwise in the monitoring conditions of this Permit. Composite sampling, where called for, shall be performed over a twenty-four (24) hour period by flow or time proportionate methods.

The test procedures for all samples shall conform to one of the USEPA approved test methods which provides the most sensitive detection limits for the pollutant under investigation listed in the current issue of the Code of Federal Regulations, and the most recent addendum published by the Federal Register. The testing for priority organic pollutants shall be conducted utilizing gas chromatograph/mass spectrometer (GC/MS) methods and procedures. Other test procedures may be approved by the USEPA, pursuant to Section 4.15.2 of the Ordinance.

D. The appropriate flow measurement devices and methods consistent with approved scientific practices shall be selected and used to ensure the accuracy and reliability of measurements of the volume of monitored discharges. The devices shall be installed, calibrated and maintained to ensure that the accuracy of the measurements are consistent with the accepted capability of that type of device. Devices select-

ed shall be capable of measuring flows with a maximum deviation of less than 10% from true discharge rates throughout the range of expected discharge volumes.

- E. For each measurement or sample taken pursuant to the requirements of this Permit, the permittee shall maintain and submit records which include:
 - 1. The date, exact place, method and time of sampling;
 - 2. The names of the person or persons taking the samples;
 - The dates analyses were performed;
 - 4. Who performed the analyses;
 - 5. The analytical techniques/methods used;
 - 6. The results of such analyses; and
 - 7. The average daily and maximum daily flows.
- F. In the event of a sampling failure, including, but not limited to, failure of sampling equipment, or sample damage, contamination, or breakage, sampling shall be repeated as soon as possible at all applicable required monitoring locations for those parameters for which the analysis of the original sample(s) was intended.
- G. The 30 day resampling requirement of Part 1.Q. of this Permit shall apply to all monitoring locations identified in this Permit. Where a violation of a plant mass limitation has occurred, all sites which contribute to the calculation of the plant mass shall be resampled concurrently. Only those parameters for which the violation has been identified are required to be analyzed as part of the resampling.
- H. Where agreed upon in advance by both parties, the POTW may perform monitoring and testing for a parameter(s) regulated by this permit and such POTW monitoring shall satisfy the self-monitoring requirement for the subject parameter(s).

PART 4 - EFFLUENT LIMITATIONS, SAMPLING AND TESTING REQUIREMENTS

A. Local Limits: The Village of Sauget reserves the right, in Ordinance 632, to establish limitations or requirements on discharges to the wastewater disposal system if deemed necessary to comply with the objectives presented in Section 1.4 of the Ordinance.

Parameter	<u>Limitations</u>	Effective date
Ammonia nitrogen	8,700 lbs/day monthly average	May 26, 1992
Ammonia nitrogen	4,300 lbs/day monthly average	July 13, 1993
Ammonia nitrogen	1,000 lbs/day monthly average	July 13, 1996

B. State Limits: These limits are stated in 35 Ill. Adm. Code Part 307. This Part 307 places restrictions on the types, concentrations, and quantities of contaminants which can be discharged into sewer systems in the State.

Limitations(mg/1)

<u>Parameters</u>	1 Day Max.	Max. Month Avg.		
Mercury	0.006	0.003		
Cyanide (Total)	10.0			

Any sample tested shall not release more than 2 mg/l of cyanide when tested at a pH of 4.5 and at a temperature of 66°C (150°F) for a period of 30 minutes.

The mercury limitation shown is the alternate limitation based on 35 Illinois Adm. Code 307.1102(c). Subject to the averaging rule of Ill Adm. Code 304.104, the monthly average shall be the numerical average of all daily composites taken during a calendar month. A monthly average must be based on at least three daily composites.

C. National Categorical Pretreatment Standards (NCPS): Monsanto's operations are subject to 40 CFR 414 - Organic Chemicals, Plastics, and Synthetic Fibers (OCPSF), Subpart G

(Bulk Organic Chemicals) and Subpart H (Specialty Organic Chemicals), which has a final compliance date for Pretreatment Standards for Existing Sources (PSES) of November 5, 1990. Sources must comply with 40 CFR Part 403 and achieve discharges not exceeding the quantity (mass) determined by multiplying the process wastewater flow subject to the OCPSF regulation times the concentration listed in the regulation, subject to application of the Combined Wastestream Formula pursuant to 40 CFR part 403.6(e), as appropriate. The Village of Sauget, as the local Control Authority, hereby exercises its discretion to calculate and apply a fixed alternative mass limit applicable to all regulated and unregulated process flows as set forth below. The applicable regulatory concentration reference values and the mass limits for your facility, determined by using average flow data you have previously provided, are set forth as follows:

Regulatory Concentration Mass Limits:

	e Values			
Parameter	Maximum Monthly Average (ug/l)	Maximum One-day (ug/l)	Maximum Monthly Average (lbs/d)	Maximum One-day (lbs/d)
Methyl Chloride Vinyl Chloride Chloroethane Methylene Chloride 1,1-Dichloroethene 1,1-Dichloroethane 1,2-trans-Dichloroethene Chloroform 1,2-Dichloroethane 1,1,1-Trichloroethane Carbon Tetrachloride 1,2-Dichloropropane 1,3-Dichloropropane 1,3-Dichloropropene 1,1,2-Trichloroethane Benzene Tetrachloroethene	(ug/1) 110 97 110 36 22 22 25 111 180 22 142 196 196 32 57	295 172 295 170 60 59 66 325 574 59 380 794 794 127 134 164		5.51 3.21 5.51 3.17 1.1 1.2 6.07 10.7 1.1 7.09 14.8 14.8 2.37 2.50 3.06 1.4
Toluene Chlorobenzene Ethylbenzene 1,3-Dichlorobenzene 1,4-Dichlorobenzene 1,2-Dichlorobenzene Hexachlorethane Nitrobenzene 2-Nitrophenol 1,2,4-Trichlorobenzene Hexachlorobutadiene 4-Nitrophenol 4,6-Dinitro-o-cresol Hexachlorobenzene Trichloroethylene Total Cyanide Total Lead Total Zinc	28 142 142 142 142 196 196 2237 65 196 142 162 78 196 26 1200 690 2610	74 380 380 380 794 794 6402 231 794 380 576 277 794 69 420 320 1050	2.65 2.65 2.65 2.65 3.66 3.66 41.75 1.2 3.66 2.65 3.02 1.5 3.66 0.49	7.09 7.09 7.09 7.09 14.8 14.8 119.5 4.31 14.8 7.09 10.7 5.17 14.8 1.3

^{1.} The Regulatory Concentration Reference Values are included in this Permit for reference purposes only. An exceedance of a Regulatory Concentration Value, without an

exceedance of the corresponding mass limit, shall not be deemed a violation of this Permit.

- 2. The mass limits are based on a maximum monthly average flow of 1554 GPM.
- 3. Cyanide, lead and zinc are not regulated at Monsanto due to the absence of cyanide and metal-bearing waste streams as listed in 40 CFR 414.
- 4. Compliance with each OCPSF parameter standard will be determined by adding the mass loadings contributed by individual processes at ten (10) locations (designated as 1 to 10 in Part 4 Section D.5. of this Permit) and comparing the composite plant mass loading to the corresponding mass limits.
- 5. The monthly average shall be the numerical average of the results of all sampling events during a calendar month. If only one sampling event occurs during a given month, the monthly average limits will apply to the results of that single sampling event.
- 6. Mass limits are subject to change based on changes in process flows. The regulated facility shall notify the POTW in writing at least sixty (60) days prior to any proposed material and/or substantial changes in process flows to allow for the calculation of revised limits.

D. Monitoring Schedule

- 1. The monitoring schedule requirements are required as of the effective date of this Permit.
- 2. Monitoring locations are indicated in the attached diagram Figure 1.
- 3. Monitoring frequencies:

Parameter (Units) Ammonia nitrogen (mg/L)	Monitoring Location 1-AA	Monitoring Frequency See 4. below	Sample Type Composite
Mercury (mg/L)	1-AA	1/month	Composite
Cyanide (mg/L)	1-AA	1/month	Grab
Flow (mgd)	1-AA	daily	Meter

- 4. Compliance with the ammonia nitrogen local limit will be determined by sampling and testing performed by the POTW. Permittee self-monitoring for ammonia is not required.
- Monitoring frequencies for OCPSF regulated monitoring locations and parameters are as follows:

OCPSF						Loc	ati	ons	/		
Parameters	Sample	Fr	equ	enc	ies						
(lb/day)	Type	1	2	3	4	_5_	6	7	8	9	10
Benzene	grab	M	M	С	С	M	С	C	С	С	C
Carbon Tetrachloride	grab	M	M	С	С	M	С	С	С	C	С
Chlorobenzene	grab	M	M	С	C	M	C	С	С	C	С
1,2,4-Trichlorobenzene	comp.	M	M	С	С	M	С	С	С	С	C
Hexachlorobenzene	comp.	M	M	С	С	M	С	C	С	C	С
1,2-Dichloroethane	grab	M	M	С	С	M	С	C	С	C	С
1,1,1-Trichloroethane	grab	M	M	С	С	M	C	С	С	C	С
Hexachlorethane	comp.	M	M	C	С	M	С	С	С	C	С
1,1-Dichloroethane	grab	M	M	C	С	M	С	С	С	С	С
1,1,2-Trichloroethane	grab	M	M	C	С	M	С	C	С	С	C C
Chloroethane	grab	M	M	С	С	M	C	С	C	С	С
Chloroform	grab	M	M	C	С	M	С	C	С	C	C
1,2-Dichlorobenzene	comp.	M	M	C	С	M	С	С	С	С	С
1,3-Dichlorobenzene	comp.	M	M	С	С	M	С	С	С	С	С
1,4-Dichlorobenzene	comp.	M	M	C	С	M	С	С	С	С	CCC
1,1-Dichloroethylene	grab	M	M	С	С	M	С	C	С	С	С
1,2-Trans-Dichloroethylene	grab	M	M	С	С	M	С	С	С	C	С
1,2-Dichloropropane	grab	M	M	С	С	M	С	С	С	С	С
1,3-Dichloropropylene	grab	M	M	С	С	M	С	С	С	С	С
Ethylbenzene	grab	M	M	С	С	M	С	С	С	С	
Methylene Chloride	grab	M	M	С	С	M	С	С	С	С	CCC
Methyl Chloride	grab	M	М	С	С	M	С	С	С	С	С
Hexachlorobutadiene	comp.	M	M	С	С	M	С	С	С	C	С
Nitrobenzene	comp.	М	M	С	С	M	С	С	С	С	C
2-Nitrophenol	comp.	М	M	С	C	M	С	С	С	С	С
4-Nitrophenol	comp.	M	M	С	С	M	С	C	С	C	C C
4,6-Dinitro-o-cresol	comp.	M	M	С	С	M	C	С	С	С	С
Tetrachloroethylene	grab	M	M	C	С	M	С	С	С	С	С
Toluene	grab	M	M	C	C	М	С	С	С	С	C
Trichloroethylene	grab	M	M	Č	Ċ	M	Č	Ċ	Č	Č	Ċ
Vinyl Chloride	grab	M	M	C	C	M	С	C	С	С	С

Monitoring locations are identified as follows:

5 - ONA/FNA - Pretreatment process 10 - Laboratory - Box 5P east pipe 7, 8, 9, and 10.

M - Monthly

1 - MCB/DCB Pretreatment process 6 - ONA/PNA - Central trench C = Flow proportioned composite
2 - NCB Pretreatment process 7 - 4NDPA - Sump from seven (7) locations on a mon3 - NCB - Acid dehy pad area 8 - 4ADPA/Santoflex - Sump thly basis. The seven locations
4 - NCB - Water separator 9 - Santoflex pastilles - Trench to be composited include 3, 4, 6, from seven (7) locations on a mon-

PART 5 - COMPLIANCE SCHEDULE

A. General:

Authority Citation: Section 4.13 Village of Sauget Pre-

treatment Ordinance No. 632.

Permit No. 92-105


Industry Name: Monsanto Company

B. Final Compliance Date: November 5, 1990 for OCPSF

C. Compliance Schedule for Ammonia-Nitrogen:

Limitations	Effective date
8,700 lbs/day monthly average	May 26, 1992
4,300 lbs/day monthly average	July 13, 1993
1,000 lbs/day monthly average	July 13, 1996

FIGURE 1 - MONITORING LOCATION







Monsanto

Monsanto Chemicai Company 500 Monsanto Ave. Sauget, Illinois 62206-1198 Phone: (618) 271-5835

October 24, 1988

Retained ancied to me.

Mr. Tom Thompson Horner & Shifrin 5200 Oakland Ave. St. Louis, MO 63110

RE: PETITION ON APPEAL FROM DISCHARGE PERMIT NO. 105

Tom:

Attached is the Petition on Appeal from the Discharge Permit for Monsanto s W. G. Krummrich Plant. If you should have any questions in regards to this submittal, please contact Paul J. Haechrel at (618) 271-5835, Ext. 2622.

Plant Manager

/dm

Enc.

G. Schillinger - American Bottoms Treatment Facility

bcc: P. J. Haechrel

S. D. Smith

P. H. Smith - E2NK

M. W. McCombs

H. M. Sheldon, Attorney at Law

MCO 0450333

BEFORE THE VILLAGE OF SAUGET

On A	Appe	al	from	Discharge))
Peri	mit	No.	105	, Monsanto))
Com	pany	, W	.G.	Krummrich	Plant)

PETITION ON APPEAL

MONSANTO COMPANY, pursuant to Ordinance No. 567, submits the following supporting facts, circumstances and authorities in support of its permit appeal concerning the W.G. Krummrich Plant Discharge Permit received from the American Bottoms Regional Treatment Facility on August 1, 1988.

MONSANTO COMPANY requests an amended permit, based on these considerations.

I. Inclusion of Specific Limitations for Categorical Pretreatment Standards Permit (Section 3)

Monsanto Company fully recognizes that the USEPA has issued National Categorical Pretreatment Standards for Organic Chemicals, Plastics and Synthetic Fibers, 40 CFR Part 414, 52 Fed. Reg. 42521 (November 5, 1987). These will apply to a significant number of manufacturing facilities at the Krummrich Plant, and are generally effective November 5, 1990.

Monsanto requests deletion of the numerous specific numerical limitations on chemical parameters set forth in

MCO 0450334

Section 3(A)(3) of the Permit, for each of the following reasons:

- (a) The OCPSF guidelines have not formally been adopted by Sauget in its Ordinance No. 567, to our knowledge. Therefore, they are not enforceable at this time. Moreover, Monsanto and others have sought judicial review of the contents of the OCPSF guidelines. They are thus subject to change.
- (b) This Permit would expire <u>before</u> the November 5, 1990 date for compliance with the OCPSF guidelines. Any issues on specific limitations may most conveniently and practicably be administratively deferred until the months immediately prior to the federal regulatory deadline for compliance, as suggested below.
- (c) Monsanto is still in the development phase of the design and installation of necessary pretreatment controls. Depending upon where pretreatment is applied and where samples to determine compliance are taken in our complex processes and/or plant, differing Alternate Limitations may apply. It is premature to apply limitations until a pretreatment system(s) and its design(s) are decided upon and installed.
- (d) The effluent limitations imposed are inaccurate, because they incorrectly interpret and

apply data on <u>concentrations</u> in Monsanto's process wastewater. Ultimately, OCPSF compliance will require calculation of limitations based on <u>mass</u> discharges from a given process. The permit inappropriately imposes general concentration limits. Furthermore, since our processes and product mix will change, the permit does not now reflect pertinent conditions, nor can it do so now.

We respectfully request the deletion of the specific limitations at page 13 and 14 of the permit, for "40 CFR §414 Organic Pollutants." We would be pleased to accept an insertion of alternative phraseology inserted at the end of the list of Parameters such as:

The permittee shall prepare a calculation of applicable limitations and/or alternate limitations, based on its compliance methodology, which shall be submitted to the Village of Sauget no later than 90 days before the federal regulatory deadline for compliance. The Village of Sauget will impose specific limitations for all applicable OCPSF chemicals relevant to permittee for the applicable time period of the permit, and the permittee shall be in compliance with OCPSF limitations by the federal regulatory deadline.

We also note that the monitoring reports and categorical deadline reports (e.g. Part 2, paras. 5, 7) in the Permit should not be deemed applicable to any chemicals regulated by the Permit solely because of the applicability of OCPSF regulation to those chemicals, until the deadline for compliance with the federal OCPSF regulation. We object to any

-3-

MC0 0450330

requirements to monitor or report on such chemicals prior to the deadline.

II. Measuring Point.

Monsanto objects to and requests deletion of identification of Outfall 1AA, shown on Figure 1 as the Monitoring Location, which is the final outfall from the Krummrich premises. This requirement presently appears to be indicated by Part 3, Section 1(A) of the Permit. USEPA regulations generally require samples to be taken immediately downstream of pretreatment facilities, with additional measurements where combined waste streams are involved. Federal regulations, 40 CFR § 403.12(b)(5)(v), states:

Samples should be taken immediately downstream from pretreatment facilities if such exist, or immediately downstream from the regulated process if no pretreatment exists.

III. Mercury Limitations.

Monsanto believes it is eligible for a 0.003 mg/l limitation on Mercury discharge, because its discharges comply with the conditions for applicability of that limitation under Illinois Pollution Control Board Rules, 35 Ill. Admin. Code, § 307.1102(c). Furthermore, the American Bottoms Treatment Facility has consistently complied with mercury limitations in its discharges, thus no need for the tighter restriction exists. Our detailed documentation in support of this request is set out as an Appendix to this Petition on Appeal. A copy

-4-

MCO 0450337

of the Appendix hereof is being submitted to the Illinois E.P.A. for their review.

Conclusion

Monsanto Company is working diligently toward compliance with the forthcoming OCPSF limitations. The entry of numerical limitations and monitoring location is inaccurate in the present permit and is premature. Also, Monsanto is eligible for an alternate, less stringent Mercury limitation, under Illinois law, as noted above.

Monsanto requests an opportunity for a hearing with the Village of Sauget in presenting this Appeal, which would include the opportunity to present additional detailed evidence should the foregoing not be fully acceptable to the Village.

Respectfully submitted,

MONSANTO COMPANY

William J. Boyle

Plant Manager

APPLICATION FOR MERCURY LIMIT EXCEPTION

FOR MONSANTO'S W. G. KRUMMRICH PLANT

DISCHARGING INTO AMERICAN BOTTOMS REGIONAL

WASTE WATER FACILITY (DISCHARGE PERMIT NO.

105) UNDER 35 ILL. ADM. CODE 307.1102(c).

APPENDIX

MCO 0450339

This application for a mercury limit exception to Monsanto's Discharge Permit No. 105 is submitted under 35 Illinois, Subtitle C, Section 307.1102(c). As per this section, exception to the 0.0005 mg/l mercury limit shall be granted if all of the following conditions are met:

- 1. The discharger does not use mercury; or the discharger uses mercury and this use cannot be eliminated; or, the discharger uses mercury only in chemical analysis or in laboratory or other equipment and takes reasonable care to avoid contamination of waste water; and
- 2. The discharge mercury concentration is less than 0.003 mg/l as determined by application of the averaging rules of 35 Ill. Adm. Code 304.104(a); and
- 3. The discharger is providing the best degree of treatment consistent with technological feasibility, economic reasonableness and sound engineering judgment. This may include no treatment for mercury; and
- 4. The discharger has an inspection and maintenance program likely to reduce or to prevent an increase in the level of mercury discharges.

The Monsanto's W. G. Krummrich Plant meets each of the conditions as explained below:

MCO 0450340

- mercury as a raw material in its processes. The use of mercury in measurement and analytical procedures and equipment is limited to certain items. Equipment is maintained and analytical procedures performed in such a manner as to avoid contamination of the waste water. If breakage and resultant spillage of mercury should occur, plant procedures require that the plant's environmental group be notified and that clean up of the spill occur to avoid contamination of the waste water.
- 2. Data for mercury concentration in the plant's waste water effluent are shown on Exhibit A for the past six months. Excluding the five days in which excursions occurred, all daily mercury levels were less than the daily maximum of 0.006 mg/l (as determined by application of averaging rules of 35Ill. Adm. Code 304.104(a)). Each excursion incident was thoroughly investigated. These excursions are believed to be caused by one or more of the following events: (1) washout of mercury contaminated caustic tanks, (2) sewer cleanouts, or (3) breakage of mercury manometer. Management controls will minimize or prevent the recurrance of mercury excursions due to these causes.

- 3. The monthly averages of the daily composites are 0.0012, 0.0008, 0.0007, 0.0029, 0.0046 and 0.0018 mg/l for the respective months of April, May, June, July, August, and September, 1988. Excluding the outlier data point of August 31, 1988, the August monthly average of 0.0017 mg/l would be in compliance with the 0.003 mg/l mercury limitation. These data show compliance with the regulated limit of 0.003 mg/l as specified in 35 Ill. Adm. Code § 307.1102(c).
- 4. Based on technological feasibility, economic reasonableness and sound engineering judgment, no treatment for mercury is required for Monsanto's W. G. Krummrich Plant. The plant wastewater discharge to the American Bottoms Regional Treatment Facility ranges from 2000 to 5000 gpm. Monsanto is aware of no economically feasible proven technology that can remove trace levels of mercury at this flow rate.
- 5. The plant already minimizes the use of instruments or measuring devices containing mercury. The use of mercury containing instruments or measuring devices will be inventoried and reevaluated for possible substitute. If an adequate replacement is available, the individual mercury source will be eliminated and properly disposed of.

In the event that a breakage and spillage should occur, the environmental group is notified. The plant has a mercury cleanup procedure which includes proper notification, cleanup, and disposal following a mercury spill. This procedure will reduce or prevent any mercury contamination affecting the wastewater effluent. Prior notification of anticipated caustic tank and sewer cleaning will be required in order to assess and further limit, if practicable, the possible impact of these activities on mercury discharge levels. Practicable management controls will be implemented.

In the event that a breakage and spillage should occur, the environmental group is notified. The plant has a mercury cleanup procedure which includes proper notification, cleanup, and disposal following a mercury spill. This procedure will reduce or prevent any mercury contamination affecting the wastewater effluent. Prior notification of anticipated caustic tank and sewer cleaning will be required in order to assess and further limit, if practicable, the possible impact of these activities on mercury discharge levels. Practicable management controls will be implemented.

EXHIBIT A

PLANT WASTEWATER EFFLUENT
MERCURY CONCENTRATION

Day	April 1983 Hg. Conc. (mg/.)	May 1988 Hg. Conc. (mg/_)	June 1988 Hg. Conc. (mg/-)
1	0.0006	0.0007	0.0009
2	0.0005	0.0006	0.0013
3	0.0010	0.0013	0.0010
4	0.0004	0.0017	-
5	0.0011	0.0004	0.0010
6	0.0014	0.0008	0.0003
7	0.0007	0.0007	0.0008
8	0.0009	0.0008	0.0025
9	0.0006	0.0001	0.0009
10	0.0006	0.0019	0.0001
11	0.0007	0.0009	0.0008
12	0.0006	0.0008	0.0004
13	0.0006	0.0006	0.0005
14	0.0044	0.0004	0.0004
15	0.0020	0.0006	0.0007
16	0.0019	0.0008	0.0008
17	0.0017	0.0004	0.0007
18	0.0038	0.0009	0.0005
19	0.0019	0.0010	0.0005
20	0.0009	0.0006	-
21	0.0009	0.0006	0.0011
22	0.0007	0.0012	0.0004
23	0.0004	0.0011	0.0006
24	0.0002	0.0005	0.0009
25	0.0015	0.0008	0.0005
2 6	0.0022	0.0003	0.0004
27	0.0009	0.0003	0.0004
28	0.0006	0.0006	. 0.0003
2 9	0.0006	0.0009	0.0008
30	0.0009	0.0009	0.0003
31	-	0.0006	•
Ave.	0.0012	0.0008	0.0007

MC0 0450344

EXHIBIT A (cont'd)

Day	July 1988 Hg. Conc. (mg/L)	August 1988 Hg. Conc. (mg/L)	September 1988 Hg. Conc. (mg/L)
1	0.0009	0.0019	0.0053
2	0.0006	0.0016	0.0028
3	0.0009	0.0010	0.0007
4	0.0011	0.0028	0.0003
5	0.0008	0.0027	0.0010
6	0.0012	0.0022	0.0015
7	0.0029	0.0011	0.0028
8	0.0059	0.0015	0.0017
9	0.0006	0.0016	-
10	0.0011	0.0017	-
11	0.0011	0.0009	0.0073 ⁽¹⁾
12	0.0022	0.0005	0.0017
13	0.0009	0.0052	0.0025
14	0.0007	0.0009	0.0059
15	0.0007	0.0038	0.0028
16	0.0007	0.0008	0.0033
17	0.0020	0.0009	0.0001
18	0.0004	0.0014	-
19	0.0011	0.0007	0.0014
20	0.0021	0.0007	0.0001
21	0.0182 ⁽¹⁾	0.0005	0.0004
22	0.0060	0.0014	0.0001
23	0.0025	0.0044	0.0005
24	0.0028	0.0042	0.0002
25	0.0165 ⁽¹⁾	0.0009	0.0002
26	0.0033	0.0013	0.0009
27	0.0081(1)	0.0017	0.0007
28	0.0005	0.0008	0.0032
29	0.0014	0.0016	0.0007
30	0.0026	0.0010	
31	0.0008	0.0895(1)	MCO 0450345
Ave.	0.0029	0.0046 0.0017 ⁽²⁾	0.0018

NOTES: 1. Excursions are believed to be caused by one or more of the following events: (1) the washout of mercury contaminated caustic tanks, (2) sewer cleanout, and (3) mercury manometer breakage. Management controls will prevent or minimize recurrence of these excursions.
2. Monthly average excluding August 31, 1988 outlier data point.

I certify under penalty of law that I have personally examined and am familiar with the information submitted in this document and that, based on my inquiry of those individuals immediately responsible for obtaining the information. I believe that the information is true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment.

DATE: October 25, 1988

SIGNATURE:

PLANT MANAGER

MCO- 0450346

Monsanto

LAW DEPARTMENT

Monsanto Company 800 N. Lindbergh Boulevard St. Louis, Missouri 63167 Phone: (314) 694-1000

August 29, 1988

HAND DELIVERED

Village Clerk Village of Sauget 2897 Falling Springs Rd. Sauget, IL 62206

> Re: Monsanto Company, Permit Appeal of Permit No. 105

Dear Madam:

Pursuant to instructions transmitted to Monsanto Company with the captioned permit, Monsanto hereby files the enclosed appeal.

1740

Please indicate the receipt of this appeal by signing the enclosed copy of this letter.

Yours very truly,

Environmental Attorney

cc: Harold G. Baker, Jr.

William J. Boyle, Jr. George R. Schillinger

Attachment

DATE:

MCD 0450347

lw/EL70/081

- 0 1/200	24 1 ማካ ቅዙ የ ካ ቆ	_AW DEPAR	TMENT I	₽.	н.	Smith		E2NK		4	-8506	_
• 'E	August	29, 1988					:		W.	J.	Boyle, Jr.	1740
		<u>.</u>							W.	C.	Engman	1740
9.65*	-	Krummrich							Μ.	R.	Foresman	G4WT
	Pretrea	atment Per	rmit Appeal	L					В.	J.	Gilhousen	E2NK
+ # # 4 + 1 ±	MWM to	MRF/PHS 8	3/12/88						P.	J.	Haechrel	1740
									G.	L.	Jones	1740
TO	M. W. 1	1cCombs	1740						Μ.	Α.	Pierle	G4WT
									s.	D.	Smith	1740

Here is a copy of Monsanto's appeal of the plant's August 1, 1988, wastewater discharge permit to be filed today pursuant to the Village Pretreatment Ordinance. Brent Gilhousen and I reviewed the required form of the appeal with Jay Baker in a telephone conversation on August 27, 1988, and the notice format is based upon guidance from Mr. Baker.

I strongly recommend that one person immediately be assigned responsibility for handling technical and administrative matters connected with follow-up of the appeal with the Village Board of Trustees. The issues involved are complex and will require substantial technical time and effort to provide adequate support.

Peter H. Smith

Attachments

MCO 0450348

Monsanto

____ LAW DEPARTMENT

Monsanto Company 800 N. Lindbergh Boulevard St. Louis, Missouri 63167 Phone: (314) 694-1000

August 29, 1988

HAND DELIVERED

Village Clerk Village of Sauget 2897 Falling Springs Rd. Sauget, IL 62206

Re: Monsanto Company, Permit Appeal of Permit No. 105

Dear Madam:

Pursuant to instructions transmitted to Monsanto Company with the captioned permit, Monsanto hereby files the enclosed appeal.

Please indicate the receipt of this appeal by signing the enclosed copy of this letter.

Yours very truly,

Peter H. Smith

Environmental Attorney

cc: Harold G. Baker, Jr. William J. Boyle, Jr. George R. Schillinger

1740

Attachment

MC0 - 0450350

lw/EL70/081

Monsanto

AW DEPARTMENT

Monsanto Company 300 N. Lindbergh Boulevard St. Louis, Missouri 63167 Phone: (314) 694-1000

August 29, 1988

President and Board of Trustees of the Village of Sauget 2897 Falling Springs Road Sauget, IL 62206

Re: Monsanto Company, Permit Appeal of Permit No. 105

Gentlemen:

Monsanto, through its attorney, objects to one or more conditions or limits of Permit No. 105 issued under authority of the Village of Sauget Pretreatment Ordinance No. 567 and requests a review by the Village Board. Monsanto further requests that the Village Board stay the effect of the permit conditions and limits during the pendency of the Appeal.

Monsanto reserves the right to supplement this request for review with other evidence and matters.

Yours very truly,

Peter H. Smith Environmental Attorney

MCO 0450351

lw/EL70/079

FROM (NAME-LOCATION-PHONE) MAX MCCOMBS - W. G. KRUMMRICH PLANT - EXT 2322

DATE

April 28, 1989

CC:

SUBJECT

WGK Discharge Permit

REFERENCE

TO

Mike Foresman Harvey Sheldon

Attached per your request is a compy of the final, effective permit for American Bottoms for the Krummerich Plant.

Max McCombs

MWM/sdg Attachments

25 Ste win squat in I

YC: M. Me CONS.
ACILITY M.S.

AMERICAN BOTTOMS REGIONAL WASTEWATER TREATMENT FACILITY

SAUGET, ILLINOIS 62201

January 16, 1989

Mr. Mark R. Schroeder Monsanto Company 500 Monsanto Avenue Sauget, Illinois 62206-1198

Dear Mr. Schroeder:

We have reviewed your Petition on Appeal from Discharge Permit No. 105 for Monsanto's W. G. Krummrich Plant. The appeal was based on three main considerations: (1) description and outline of specific limitations for Organic Chemicals, Plastics, Synthetic Fibers (OCPSF) National Categorical Pretreatment Standard (NCPS); (2) monitoring location; and (3) State Illinois mercury limitations for indirect dischargers.

In regard to item (1), the permit did not require monitoring of OCPSF parameters until the effective date of the regulation. However, since a change in the limitation conditions is currently anticipated prior to the effective date, numerical limitations have been deleted from the permit and the associated wording regarding the OCPSF monitoring and sampling requirements have been modified accordingly.

In regard to item (2), monitoring location 1-AA is still needed for other current monitoring requirements. However, its designation as a future monitoring location for OCPSF parameters has been deleted as requested since a new monitoring location may be proposed prior to the effective date of the OCPSF regulation.

In regard to item (3), we find, based on information submitted as part of the appeal, that the conditions of 35 Ill. Adm. Code 307.1102 (C) have been satisfied, thereby allowing the alternate numerical limit of 0.003 mg/L. The permit has been revised accordingly to include the approved alternate limitation.

Enclosed are two (2) copies of the revised permit.

If you have any questions or comments, please call.

Very truly yours, VILLAGE OF SAUGET

 \sim


MAYGUNC

GRS:ko Enclosure

MCG 0450126

CITY OF EAST ST. LOUIS - VILLAGE OF SAUGET
COMMONFIELDS OF CAHOKIA PUBLIC WATER DISTRICT

VILLAGE OF CAHOKIA
METRO EAST SANITARY DISTRICT



VILLAGE OF SAUGET

AMERICAN BOTTOMS REGIONAL WASTEWATER DISCHARGE PERMIT

TABLE OF CONTENTS

	<u>Page</u>
TABLE OF CONTENTS	1
PERMIT	2
PART 1 - GENERAL CONDITIONS OF PERMIT	3-4
PART 2 - GENERAL REPORTING REQUIREMENTS	4-5
PART 3 - SAMPLING AND TESTING REQUIREMENTS Section 1 - General	5-15
Section 2 - Initial Pollutant Screening	
Section 3 - Compliance Sampling	
A. Effluent Discharge Limits	
B. Monitoring Requirements	
C. Monitoring Schedule	
PART 4 - COMPLIANCE SCHEDULE	16
FIGURE 1 - MONITORING LOCATION PLAN	17

- 1 -

VILLAGE OF SAUGET

AMERICAN BOTTOMS REGIONAL WASTEWATER DISCHARGE PERMIT				
Permit No. 105				
In accordance with all terms and conditions of Ordinance 567 of the Village of Sauget; the 1977 Regional Agreement as amended; Section 46 of the Illinois Environmental Protection Act of 1970 (III. Rev. Stat. 1987. Ch. 1111/2, Sec. 1046) as amended; and III. Rev. Stat. 1987, Ch. 24, Sec. 11-141-7; permission is hereby granted to:				
Monsanto Chemical Company - W.G. Krummrich Plant (name of industry)				
500 Monsanto Avenue (address)				
Sauget, Illinois 62206-1198				
Classified Standard Identification Code (SIC) No. <u>2819, 2842, 2865, 2869</u>				
Subject to the National Categorical Pretreatment Standard (NCPS) No				
40 CFR 414				
to discharge industrial wastewater into sewer lines tributary to the American Bottoms Regional Wastewater Treatment Plant.				
This permit is granted in accordance with the application filed on the <u>28th</u> day of the month of <u>March</u> , in the year of 19 <u>88</u> in the office of the Regional Plant Manager, #1 American Bottoms Road, Sauget, Illinois 62201, and in conformity with plans, specifications and other data submitted in support of the above application, all of which are filed with and considered as a part of this permit, together with the attached conditions and requirements.				
Nothing herein shall be construed as a permit or is permission for the permittee to violate the provisions of any sewer use ordinance in effect within the jurisdiction of any unit of local government in which the permittee's facility is located.				
Effective this <u>lst</u> day of <u>August</u> , 19 <u>88</u>				
To expire the <u>lst</u> day of <u>August</u> , 19 <u>89</u>				
By: Regional Plant Manager				

PART 1 - GENERAL CONDITIONS OF PERMIT

- 1. General This Wastewater Discharge Permit shall be expressly subject to all provisions of Ordinance 567 of the Village of Sauget and all other applicable regulations, user charges, and fees established by the Village of Sauget. In consideration of the granting of this permit and compliance with the Ordinance, the permittee shall comply with all provisions of the Ordinance, permit conditions, and the Standard Operating Procedures including but not limited to the specific requirements of these General Condition Articles.
- 2. <u>Prohibitive Standards</u> The permittee shall comply with all prohibitive discharge standards pursuant to Paragraph 3.2 of the Ordinance and all Local, State, and Federal discharge limits as outlined in the Permit.
- 3. <u>Monitoring Facilities</u> The permittee shall install and operate monitoring facilities and afford the POTW access thereto; pursuant to Paragraph 4.5 of the Ordinance.
- 4. <u>Inspection of Facilities and Records</u> The permittee shall allow the POTW or its representatives ready access upon presentation of credentials at reasonable times to all parts of its premises in which a discharge source or treatment system is located or in which records required by this Ordinance are kept for the purposes of inspection, sampling, examination and photocopying of said records and for the performance of any of their duties; pursuant to Paragraph 4.6.1 of the Ordinance.
- 5. Retention of Records The permittee shall retain for a minimum of three years any records of monitoring activities and results relating to wastewater discharge and for affording the POTW access to said records; pursuant to Paragraphs 4.6.3, 4.6.4 of the Ordinance.
- 6. Change in Conditions The permittee shall provide advance notification to the POTW of any material and substantial change in the type, quality, or volume of the wastewater constituents being introduced into the wastewater treatment system; pursuant to Paragraph 4.2.6 of the Ordinance.
- 7. <u>Prohibition of Improper Dilution</u> Improper dilution shall be prohibited pursuant to Paragraph 3.8 of the Ordinance.
- 8. <u>Spill Containment and Unlawful Discharge</u> Spill Containment procedures and notification of slug, accidental and/or deliberate discharges shall be required pursuant to Paragraph 3.9 of the Ordinance.

- 9. <u>Transfer</u> Wastewater Discharge Permits are issued to a specific Significant Industrial User for the process activity specified in the permit. A Wastewater Discharge permit shall not be assigned, transferred or sold to a new owner or new user in different premises or to a new or changed operation in the same or different premises without the approval of the Village of Sauget; pursuant to Paragraph 4.2.9 of the Ordinance.
- 10. <u>Permit Modifications</u> The terms and conditions of this permit may be subject to modifications by the Village of Sauget during the term of this permit; pursuant to Section 4.2.8 of the Ordinance.
- 11. Pretreatment The permittee shall comply with all necessary pretreatment requirements pursuant to Paragraph 3.7 of the Ordinance.
- 12. Additional Information The permittee shall furnish any additional information as may be reasonably requested by the Village of Sauget from time to time.

PART 2 - GENERAL REPORTING REQUIREMENTS

- 1. <u>General</u> The General Pretreatment Regulations of 40 CFR 403.12 and Ordinance 567 have set forth basic reporting requirements that apply to Significant Industrial Users (SIUs). Reporting requirements include the following General Reporting Requirements.
- 2. Periodic Compliance Report The permittee shall submit to the Village of Sauget during the months of June and December for the preceding two calendar quarters unless required more frequently in the Pretreatment Standard or by the POTW or IEPA, a certified report indicating the nature and concentration of pollutants in the effluent which are limited by such applicable Pretreatment Standards. In addition, this report shall include a record of measured or estimated average and maximum daily flows for the reporting period. The requirements of this reporting are described in Paragraph 4.4.3 of the Ordinance and the Standard Operating Procedures, Part III, Paragraph 3.4.3.
- 3. <u>Incremental Compliance Report</u> This report is required should the Baseline Monitoring Report (if applicable) or the Periodic Compliance Report reflect that the Significant Industrial User is not in compliance with its pretreatment standards and/or its compliance schedule. The requirements for this report are described in the Standard Operating Procedures, Part III, Paragraph 3.4.4 and Paragraph 4.4.2.
- 4. Notice of Unlawful Discharge The permittee shall submit to the Village of Sauget an oral report detailing any unlawful discharge and a follow-up written report as described in Paragraph 3.9 of the Ordinance and Part III, Paragraph 3.4.6 of the Standard Operating Procedures.

[Revised 12-22-88]

- 4 -

MCO 0450130

- 5. Monitoring Reports Monitoring results obtained shall be summarized and reported on a monthly basis. The report is due on or before 45 days after the sampling was performed. The report shall indicate the nature and concentration of all pollutants in the wastewater discharges which are regulated by the standards set forth in this Permit and include measured maximum and average daily flows.
- 6. <u>Baseline Monitoring Report</u> The permittee shall submit to the Village of Sauget, a report that indicates whether the industrial user meets their particular categorical standard. The specific elements of the report are contained in Paragraph 4.4.1 of the Ordinance and Part III, Paragraph 3.4.2 of the Standard Operating Procedures.
- 7. <u>Categorical Deadline Report</u> The permittee shall submit to the Village of Sauget, a report on forms provided by the Village of Sauget indicating the nature and concentration of all limited pollutants in the regulated discharges and the average and maximum daily flow for these discharges. The report also must indicate whether the pretreatment standards are being met consistently.
- 8. Report Submittal All reports required by this Permit shall be submitted in triplicate to:

Village of Sauget c/o American Bottoms Regional Wastewater Treatment Facility #1 American Bottoms Road Sauget, Illinois 62201 Attn: Pretreatment Coordinator

PART 3 - SAMPLING AND TESTING REQUIREMENTS

Section 1 - General

- A. The sampling responsibilities of all Significant Industrial Users (SIUs) have two parts: 1) an initial pollutant screening; and 2) compliance sampling. The monitoring facilities designated by this permit are shown on Figure 1.
- B. The initial pollutant screening is a comprehensive sampling and testing for priority organic pollutants, metals, cyanide, and phenols, and conventional pollutants. Pollutants, frequencies, sample type and schedule for the initial screening are outlined in Section 2. The permittee shall initiate the initial pollutant screening by August 15, 1988

Sampling schedule may be adjusted by POTW if it appears that certain organic fractions are not relevant. "X" indicates that sampling and testing needs to be performed for that particular month. "N.A."

indicates that sampling and testing is not applicable for a particular organic fraction in a particular month. All organic fractions that require monitoring shall be sampled in the same twenty-four (24) hour time period as the composite sample. The testing for priority organic pollutants shall be conducted utilizing gas chromatograph/mass spectrometer (GC/MS) methods and procedures.

C. Compliance sampling addresses the sampling and testing requirements to demonstrate continued compliance with pretreatment standards. Compliance sampling relates to pollutants for which local, state, and national categorical limits exist, and any other parameters identified by the Village of Sauget in this permit. First year SIU sampling frequencies for compliance sampling are based on the average total wastewater flow to the Village of Sauget during the previous twelve (12) month period. First year sampling frequency for compliance sampling are given below and they apply to all parameters which the SIU is subject to specific limitation.

Flow (GPD)	Conventional Pollutants Metals, Cyanide, and Phenols	<u>Organics</u>
0 - 10,000 10,0001 - 50,000	one/month one/month	two/year two/year
50,0001 - 100,000	two/month	four/year
100,000 - 240,000	one/week	six/year
over 240,000	one/week	one/month

- D. Compliance monitoring results and frequencies shall be reviewed annually by the Village of Sauget and appropriate adjustments made to frequencies and parameters in an updated Wastewater Discharge Permit. Pollutants and frequencies for compliance sampling are cited hereafter. The SIU shall submit a monitoring schedule to the Village of Sauget for review and approval. The schedule shall identify the dates that are proposed for sampling.
- E. All handling and preservation of collected samples and laboratory analyses shall be performed in accordance with procedures contained in 40 CFR Part 136 and amendments thereto unless specified otherwise in the monitoring conditions of this permit. Composite sampling, where called for, shall be performed over a twenty-four (24) hour period by flow or time proportionate methods. The test procedures for all samples shall conform to one of the approved test methods which provides the most sensitive detection limits for the pollutant under investigation listed in the current issue of the Code of Federal Regulations, and the most recent addendum published by the Federal Register. Grab samples will be required once every twenty-four (24) hour period for testing of Volatile Organic Compounds; Fecal Coliforms; Oil and Grease; and pH, in the same twenty-four (24) hour period as the composite sampling is performed. Other procedures may be exercised, pursuant to Section 4.6.2 of the Ordinance.

- F. The appropriate flow measurement devices and methods consistent with approved scientific practices shall be selected and used to ensure the accuracy and reliability of measurements of the volume of monitored discharges. The devices shall be installed, calibrated and maintained to ensure that the accuracy of the measurements are consistent with the accepted capability of that type of device. Devices selected shall be capable of measuring flows with a maximum deviation of less than 10% from true discharge rates throughout the range of expected discharge volumes.
- G. For each measurement or sample taken pursuant to the requirements of this permit, the permittee shall maintain and submit records which include:
 - 1. The date, exact place, method and time of sampling;
 - 2. The names of the person or persons taking the samples;
 - The dates analyses were performed;
 - 4. Who performed the analyses;
 - 5. The analytical techniques/methods used; and
 - 6. The results of such analyses.
 - The average daily and maximum daily flows.

SECTION 2 - INITIAL POLLUTANT SCREENING

	Parameters	Sampl AUG 88	ing Sche OCT 88	<u>DEC 88</u>	Frequency	Sample Type
1.	Priority Organic Pollutants (See Table 1)					
	Acid Compounds	<u> </u>	<u> </u>	X	1/Month	Composite
	Base/Neutral	<u> </u>	<u> </u>	X_	1/Month	Composite
	Pesticides	<u> X</u>	<u> X</u>	X_	1/Month	Composite
	Volatiles	<u> </u>	X	<u>X_</u>	1/Month	Grab
2.	Conventional Pollutants (See Table 2)	X	X	X_	1/Week	Composite ¹
3.	Metals, Cyanide, and Phenols (See Table 3)	X	X_	X_	1/Week	Composite
4.	Other Parameters requested by POTW					
	Ammonia Nitrogen	<u> </u>	<u> </u>	X_	1/Week	Composite
	Organic Nitrogen	<u>X</u>	X	X_	1/Week	Composite

MCO 0450134

Grab samples required for pH, Fecal Coliform, Oil and Grease.

TABLE 1

PRIORITY ORGANIC POLLUTANTS (40 CFR 122, App. D, Tbl. II)

Acid Compounds

2-chlorophenoi 2,4-dichlorophenol 2,4-dimethylphenol 4,6-dinitro-o-cresol 2,4-dinitrophenol 2-nitrophenol 4-nitrophenol p-chloro-m-cresol pentachlorophenol phenol 2,4,6-trichlorophenol

Base/Neutral

acenaphthene acenaphthylene anthracene penzidine benzo(a)anthracene benzo(a)pyrene 3.4-benzofluoranthene benzo(ghi)perylene benzo(k)fluoranthene bis(2-chloroethoxy)methane bis(2-chloroethyl)ether bis(2-chloroisopropyl)ether bis (2-ethylhexyl)phthalate 4-bromophenyl phenyl ether butylbenzyl phthalate 2-chloronaphthalene 4-chlorophenyl phenyl ether chrysene dibenzo(a,h)anthracene 1.2-dichlorobenzene 1.3-dichlorobenzene 1.4-dichlorobenzene 3,3'-dichlorobenzidine diethyl phthalate dimethyl phthalate di-n-butyl phthalate 2,4-dinitrotoluene 2.6-dinitrotoluene

hexachlorobenzene
hexachlorobutadiene
hexachlorocyclopentadiene
hexachloroethane
indeno(1,2,3-cd)pyrene
isophorone
napthalene
nitrobenzene
N-nitrosodimethylamine
N-nitrosodi-n-propylamine
N-nitrosodiphenylamine

di-n-octyl phthalate

fluroranthene

fluorene

1,2-diphenylhydrazine (as azobenzene)

pyrene
1.2.4-trichlorobenzene

phenanthrene

Volatiles

acrolein

acrylonitrile benzene bromoform carbon tetrachloride chlorobenzene chlorodibromomethane chloroethane 2-chloroethylvinyl ether chloroform dichiorobromomethane 1.1-dichloroethane 1.2-dichloroethane 1.1-dichloroethylene 1.2-dichloropropane 1.3-dichloropropylene ethylbenzene methyl bromide methyl chloride methylene chloride 1.1,2,2-tetrachioroethane tetrachloroethylene toluene 1,2-trans-dichloroethylene 1.1.1-trichloroethane 1.1.2-trichloroethane trichtgroethylene vinyl chloride

Pesticides

aldrin alpha-BHC beta-BHC gamma-BHC delta-BHC chlordane 4.4"-DDT 4.4"-DDE 4.4'-DDD dieldrin ainha-endosulfan beta-endosulfan endosulfan sulfate endrin endrin aldehyde heptachlor heptachlor epoxide PCB-1242 PCB-1254 PCB-1221 PCB-1232 PCB-1248 PCB-1260 PCB-1016 loxaphene

MCO 0450135

TABLE 2

CONVENTIONAL POLLUTANTS (40 CFR 401.1b)

Biochemical oxygen demand (BOD)
Total suspended solids (nonfilterable) (TSS)
pH
Fecal Coliform
Oil and Grease

- 10 -

TABLE 3

METALS, CYANIDE, PHENOLS (40 CFR 122, App. D, Tbl. III)

Antimony, Total Arsenic, Total Beryllium, Total Cadmium, Total Chromium, Total Copper, Total Lead, Total Mercury, Total Nickel, Total Selenium, Total Silver, Total Thallium, Total Zinc, Total Cyanide, Total Phenols, Total

SECTION 3 - COMPLIANCE SAMPLING

A. <u>Effluent Discharge Limits</u>

1. Local Limits: The Village of Sauget reserves the right, by Ordinance 567, to establish limitations or requirements on discharges to the wastewater disposal system if deemed necessary to comply with the objectives presented in Section 1.1 of the Ordinance.

Parameter

Limitations

N.A.

 State Limits: These limits are stated in 35 Ill. Adm. Code Part 307. This Part 307 places restrictions on the types, concentrations, and quantities of contaminants which can be discharged into sewer systems in the State.

<u>Parameter</u>	<u>Limitations</u>					
Mercury	0.003 $(mg/L)^{1}$ (Max. Month Avg.)					
Cyanide (Total)	10.0 (mg/L) ² (Max. Grab)					

3. National Categorical Pretreatment Standards (NCPS): NCPS are standards published by USEPA and contain numerical limits for the discharge of pollutants from specified industrial categories. These categorical standards have been or will be developed for industrial categories determined to be the most significant sources of pollutants. Your operations are subject to 40 CFR 414 which includes the following parameters:

- 12 -

[Revised 12-22-88]

Alternate limitation based on 35 Il. Adm. Code 307.1102(c).

Provided any sample tested shall not release more than 2 mg/L of cyanide when tested at a pH of 4.5 and at a temperature of 66 C (150 F) for a period of 30 minutes.

40 CFR 414 Organic Pollutants:

Acenaphthene Benzene Carbon Tetrachloride Chlorobenzene 1.2.4-Trichlorobenzene Hexachlorobenzene 1.2-Dichloroethane 1,1,1-Trichloroethane Hexachlorethane 1,1-Dichloroethane 1,1,2-Trichloroethane Chloroethane Chloroform 1,2-Dichlorobenzene 1,3-Dichlorobenzene 1,4-Dichlorobenzene 1,1-Dichloroethylene 1,2-Trans-Dichloroethylene 1,2-Dichloropropane 1,3-Dichloropropylene 2.4-Dimethylphenol Ethylbenzene

Fluoranthene Methylene Chloride Methyl Chloride Hexachlorobutadiene Naphthalene Nitrobenzene 2-Nitrophenol 4-Nitrophenol 4.6-Dinitro-o-cresol Phenol Bis(2-ethylhexyl) phthalate Di-n-butyl phthalate Diethyl phthalate Dimethyl phthalate Anthracene Fluorene Phenanthrene Pyrene Tetrachloroethylene Toluene Trichloroethylene Vinyl Chloride

40 CFR 414 Other Pollutants:

Total Cyanide Total Lead Total Zinc

The permittee shall prepare a calculation of applicable limitations and/or alternate limitations, based on its compliance methodology, which shall be submitted to the Village of Sauget no later than 90 days before the federal regulatory deadline for compliance. The Village of Sauget will impose specific limitations for all applicable OCPSF chemicals relevant to permittee for the applicable time period of the permit, and the permittee shall be in compliance with OCPSF limitations by the federal regulatory deadline.

MCO 0450139

[Revised 12-22-88]

B. Monitoring Requirements

The compliance monitoring requirements for Mercury and Cyanide are required as of the effective date of this permit. Compliance monitoring requirements for Organic Pollutants and Other Pollutants will be required by the federal regulatory deadline of the OCPSF Standards.

	Limitations				
<u>Parameters</u>	1 Day Max.	Max. Month Avg.	Max. Grab		
Mercury ^l Cyanide (Total)	0.006 (mg/L)	0.003 (mg/L)	0.015 (mg/L) 10.0 (mg/L) ²		

C. Monitoring Schedule

The monitoring schedule requirements for Mercury, Cyanide, and Flow are required as of the effective date of this permit. A monitoring schedule for Organic Pollutants and Other Pollutants will be required by the federal regulatory deadline of the OCPSF Standards.

Parameter (Units)	Monitoring Location 3	Frequency	Sample Type
Mercury (mg/L)	1 - AA	1/Week	Composite
Cyanide (mg/L)	1- AA	1/Week	Composite
Flow (mgd)	1 - AA	Daily	Me ter

MCG 0450140

[Perised 12-22-88]

Alternate limitation based on 35 Il.Adm. Code 307.1102(c).

Provided any sample tested shall not release more than 2 mg/L of cyanide when tested at a pH of 4.5 and at a temperature of 66 C (150 F) for a period of 30 minutes.

See attached diagram - Figure 1.

PART 4 - COMPLIANCE SCHEDULE

A. General:

Authority Citation: Section 4.2.5, Village of Sauget Pretreatment Ordinance No. 567.

Permit No. 105

Industry Name: Monsanto Chemical Company

B. <u>Compliance Schedule</u>:


<u>Event</u>	Complete By No Later Than
Define project premises	3/01/89
Complete project scope/estimates appropriation requests	12/01/89
Project designs	6/01/90
Project constructions	9/01/90
Startup facilities	11/05/90

Compliance schedule based on June 7, 1988 Baseline Monitoring Report (BMR) and the current OCPSF regulations published November 5, 1987.

C. Compliance Schedule Reporting: No later than 14 days following each date in the above schedule, the permittee shall submit to the POTW a progress report including, at a minimum, whether or not it complied with the increment of progress to be met on such date and, if not, the date on which it expects to comply with the increment of progress, the reasons for delay, and the steps being taken to return the project to the schedule established.

MCO 0450141

[Revised 12-22-88]



MCO 0450142 dIGURE 1